

NASA TECH BRIEF

Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Rechargeable, Silver-Zinc Battery Conditioner/Monitor Unit and State-of-Charge Indicator

A new conditioner/monitor unit has been developed for use with rechargeable silver-zinc batteries. The unit automatically charges the batteries to the desired state-of-charge levels, monitors functional battery parameter data both on meters and a printer, and automatically activates an alarm in the event of battery malfunctions. The unit consists of six assemblies:

1. the state-of-charge indicator panel,
2. the control panel,
3. the monitor panel,
4. the power panel,
5. the charging-current power supply, and
6. the load panel.

The state-of-charge indicator-panel assembly computes the state-of-charge by summing the charging and discharging ampere-hours. It provides output pulses for each predetermined incremented quantity of ampere-hours applied to, or removed from a battery. The outputs from the state-of-charge assembly are applied to the monitor and control panels.

The control-panel assembly provides both automatic and manual controls to determine the charging and discharging modes of a system. In addition, it determines charging-current magnitude.

The monitor-panel assembly acquires, conditions, processes, and displays battery parameter data. It incorporates a multiplexer (scanner), which has 30 channels (25 of which are used), to time share battery parameter data. In addition, a digital voltmeter is incorporated; it has a range of 0 to 19.999 volts and an accuracy of 0.01 percent.

The power-panel assembly regulates the output voltage, limits the overload current, and protects against

overvoltage. It supplies three signals: (1) a +5-volt, dc, 12-ampere supply; (2) a +15-volt, dc, 2-ampere supply; and (3) a -15-volt, dc, 2-ampere supply.

The charging-current power-supply assembly has a 21-ampere dc output. It is adjustable over the range of 40 to 44 volts, dc, regulated to ± 1 percent.

The load-panel assembly provides a control for the input power to the charging-current power supply, switches a battery between the charger and the load, provides a load resistor for battery discharge, and regulates the charging current.

The entire conditioner/monitor unit includes commercially available assemblies to reduce overall system cost. Wherever possible, the system incorporates integrated circuits.

Note:

Requests for further information may be directed to:
Technology Utilization Officer
Marshall Space Flight Center
Code A&PS-TU
Marshall Space Flight Center, Alabama 35812
Reference: B73-10486

Patent status:

NASA has decided not to apply for a patent.

Source: C. E. Thomas of
Chrysler Corp.
under contract to
Marshall Space Flight Center
(MFS-22835)